

		Sistemi REBLOC	Stopnja zadrževanja	Delovna širina	ASI	Konstrukcija	Dimenzija betonski element d/s/v [cm]	Teža/element (pribl.) [kg]	Min. dožina montaže [m]	Širina sistema [cm]			
Standardni elementi	Začasni sistemi	RB50	_12	T1	W1	A	sym F	1200 / 24 / 50	1.500	180	24		
			_12	T3	W2	A	sym F	1200 / 24 / 50	1.500	180	24		
		RB60	_4	-	-	-	sym F	417 / 26 / 60	780	-	26		
			-	T1	W1	A	sym F	600 / 26 / 60	1.090	120	26		
			_6	T3	W2	A	sym F	600 / 26 / 60	1.090	120	26		
			-	T1	W1	A	sym F	1200 / 26 / 60	2.180	120	26		
		RB60H	-	T3	W2	A	sym F	1200 / 26 / 60	2.180	120	26		
			_12	N2	W42	B	sym F	1200 / 26 / 50	2.180	120	26		
		RB80S	-	T3	W2	B	sym F	1200 / 30 / 80	3.000	120	30		
			-	N2	W4	B	sym F	1200 / 30 / 80	3.000	120	30		
			_12	H1	W4	B	sym F	1200 / 30 / 80	3.000	120	30		
			-	T1	W1	A	sym F t2p	800 / 57 / 85	4.600	80	57		
		RB85BFS	-	T3	W2	A	sym F t2p	800 / 57 / 85	4.600	80	57		
			-	T1	W1	A	asym F t2p	800 / 44 / 85	4.000	80	44		
		RB85BF	-	T3	W1	A	asym F t2p	800 / 44 / 85	4.000	80	44		
			-	T3	W1	A	asym F t2p	800 / 44 / 85	4.000	80	44		
	Trajni sistemi	RB80L	_4	N2	W4	B	sym F	400 / 56 / 80	1.500	68	56		
			-	H1	W5	B	sym F	800 / 56 / 80	4.000	80	56		
			_2	-	-	-	sym F	200 / 56 / 80	1.050	-	56		
			-	-	-	-	sym F	400 / 56 / 80	2.100	-	56		
		RB80L	-	N2	W3	B	sym F	800 / 56 / 80	4.000	112	56		
			-	H1	W4	B	sym F	800 / 56 / 80	4.000	112	56		
			_2	-	-	-	sym F	200 / 56 / 80	1.050	-	56		
			-	-	-	-	sym F	400 / 56 / 80	2.100	-	56		
		RB80H	-	H2	W5	B	sym F	800 / 56 / 80	4.000	80	56		
			_4	-	-	-	sym F	400 / 56 / 80	2.100	-	56		
			-	H2	W5	B	sym F	800 / 56 / 80	4.000	80	56		
			-	H2	W3	B	sym AS	800 / 56 / 80	4.000	64	56		
		RB84XEAL	-	H2	W1	B	sym EA	800 / 59 / 84	4.800	40	59		
			-	H2	W5	B	sym BF t2p	800 / 57 / 85	4.600	56	≥ 160 cm		
			-	H2	W5	B	sym BF t2p	800 / 44 / 85	4.000	56	≥ 160 cm		
			-	H2	W5	B	sym BF t2p	800 / 44 / 85	4.000	56	≥ 160 cm		
		RB100H	-	H3	W6	B	sym F	200 / 64 / 100	1.500	76	64		
			_2	H2	W5	B	sym F	200 / 64 / 100	1.050	64	64		
			-	-	-	-	sym F	400 / 64 / 100	3.100	-	64		
			-	N2	W3	B	sym F	800 / 64 / 100	6.000	104	64		
		RB100	-	H1	W4	B	sym F	800 / 64 / 100	6.000	104	64		
			-	H4b	W5	B	sym F	800 / 68 / 100	6.750	96	68		
			-	H2	W5	B	sym F	800 / 64 / 100	6.000	80	64		
			-	H4b	W6	B	sym F	800 / 64 / 100	6.000	104	64		
		RB100SFS	-	H4b	W5	B	sym F	800 / 68 / 100	6.750	96	68		
			-	H4b	W5	B	sym F	800 / 68 / 100	6.750	96	68		
			-	H4b	W5	B	sym F	800 / 68 / 100	6.750	96	68		
			-	H4b	W5	B	sym F	800 / 68 / 100	6.750	96	68		
	Protihrupna ograja	NB100Q/300	-	H2	W4	B	asym F	800 / 95 / 300	13.500	64	95		
		NB100H/300	-	H3	W5	C	sym F	800 / 95 / 300	19.550	64	95		
		Terminalski elementi	Začasni sistemi	RB50	_2T	-	-	-	sym F	200 / 24 / 15-50	350	-	24
				RB60	_3T	-	-	-	sym A	300 / 26 / 11-60	660	-	26
RB80S	_4T			-	-	-	sym A	400 / 30 / 21- 80	760	-	30		
RB85BFS	_4T			-	-	-	sym F t2p	400 / 57 / 25-85	2.050	-	57		
RB85BF	_4T			-	-	-	asym F t2p	400 / 44 / 25-85	1.800	-	44		
RB80H	_4T			-	-	-	sym A	400 / 56 / 20-80	1.800	-	56		
Trajni sistemi	-		_7T	-	-	-	sym A	700 / 56 / 23-80	3.100	-	56		
	RB84XEAL		_4T	-	-	-	sym EA	400 / 59 / 24-84	2.300	-	59		
	RB85BFS		_4T	-	-	-	sym F t2p	400 / 57 / 25-85	2.050	-	≥ 160 cm		
	RB85BF		_4T	-	-	-	sym F t2p	400 / 44 / 25-85	1.800	-	≥ 160 cm		
	RB100		_4T	-	-	-	sym A	400 / 64 / 24-100	2.400	-	64		
	RB100SFS		_4T	-	-	-	sym A	400 / 68 / 24-100	2.470	-	68		
	RB110L		_4,5T	-	-	-	sym A	450 / 64 / 24-110	2.800	-	64		
	RB100SF		_4T	-	-	-	asym A	400 / 56 / 24-100	2.300	-	56		
	Most		-	-	-	-	-	-	-	-	-		
			-	-	-	-	-	-	-	-	-		

		Sistemi REBLOC	Stopnja zadrževanja	Delovna širina	ASI	Konstrukcija	Dimenzija betonski element d/s/v [cm]	Teža/element (pribl.) [kg]	Min. dožina montaže [m]	Širina sistema [cm]		
Prehodni elementi	Protihrupna ograja	RB50_60H	_1,27	-	-	-	sym F	127 / 24-26 / 50-60	230	-	26	
		RB60H_80S	_2,47	-	-	-	sym F	247 / 26-30 / 60-80	630	-	30	
		RB60H_80H	_3	-	-	-	sym F	300 / 26-56 / 60-80	1.260	-	56	
		RB80_100	_4	-	-	-	sym F	400 / 56-64 / 80-100	2.600	-	64	
		RB80H_100	_4	-	-	-	sym F	400 / 56-64 / 80-100	2.600	-	64	
		RB100_110	_2	-	-	-	sym F	200 / 64 / 100-110	1.600	-	64	
		RB100_110L	_2	-	-	-	sym F	200 / 64 / 100-110	1.600	-	64	
		Protihrupna ograja	RB100_RNB100/300_3	-	-	-	-	asym F	309 / 64-95 / 100	3.520	-	95
	RB100_RNB100H/300_3		-	-	-	-	asym F	309 / 64-95 / 100	3.520	-	95	
	Prehod na jeklo		RB60	_2,65EDSP	-	-	-	sym F	265 / 26 / 60-75	850	-	26
			RB80	_4S	-	-	-	sym F	400 / 30-56 / 80	2.100	-	56
		RB80H	_4S	-	-	-	sym F	400 / 30-56 / 80	2.150	-	56	
		RB84XEAL	_4S	-	-	-	sym EA	400 / 33-59 / 84	2.650	-	59	
	Voest	RB100	_4S	-	-	-	sym F	400 / 34-64 / 100	3.050	-	64	
		RB100	_KB3 RH2B	H2	W4	C	asym F	400 / 64 / 100	3.100	24,318	64	
		In-situ	RB100H	_ISA_2	-	-	-	sym F	200 / 64 / 100	1.600	-	64
			RB100	_ISA_6	-	-	-	sym F	800 / 64 / 100	6.150	-	64
	Bifurkacijski elementi	RB80H	_4B	-	-	-	sym F	400 / 56-96 / 80	3.600	-	96	
			-	-	-	-	asym F	400 / 43 / 80	1.900	-	43	
			_4B	-	-	-	sym F	400 / 64-104 / 100	5.000	-	104	
			-	-	-	-	asym F	400 / 51 / 100	2.900	-	51	
	Dilatacijski elementi	RB80A	_2EXM	H2	W1	B	asym A	410 / 43 / 80	2.000	-	43	
			RB100A	_2EXM	H2	W1	B	asym A	410 / 51 / 100	3.000	-	51
			RB100SF*	_EXM	H4b	W4	B	asym A	485-605 / 56 / 100	4.000-5.000	-	56
RB100SFS*			_EXM	H4b	W5	B	sym A	485-605 / 68 / 100	4.300-5.375	-	58	
Lahki stebni elementi	RB80	_8LC	-	-	-	sym F	800 / 56 / 80	6.000	-	56		
		RB80H	_8LC	-	-	-	sym F	800 / 56 / 80	6.150	-	56	
		RB100	_6LC	-	-	-	sym F	600 / 64 / 100	7.350	-	64	
		RB100A	_6LC	-	-	-	sym A	600 / 64 / 100	7.400	-	64	
Prometni znaki	RB100	_6TS	-	-	-	sym F	600 / 64 / 100	7.350	-	64		
		RB100A	_6TS	-	-	-	sym A	600 / 64 / 100	7.400	-	64	